

# ELI-1614 Conformal Battery

Rechargeable Semi-Flexible Li-ion Battery Pack

## General description

- Semi-Flexible tactical battery pack
- High energy high Power density
- One wire / SMBus communication technology
- Smart circuit providing remaining capacity, number of cycles and health status
- LED State Of Charge Indicator (SOCi)
- Low energy consumption during storage
- Easy integration into compact and light systems
- Meets civil and military standards



## Applications

Wearable conformal military battery supporting communications, tactical computers, ISR and additional devices carried by soldiers

## Charge Method (CCCV)

- Charging through a desktop or tactical charger or through a dedicated charging board installed in host device
- Charging Voltage: 16.8V
- Typical charging current: C/3

## Safety

- Under/over voltage
- Under/over current
- Short circuit
- Temperature
- Reverse polarity

## Quality System

- ISO-9001:2008

## Applicable Standards

- UN-38.3
- MIL-STD-810E
- UL-1642 (for cells)

## MSDS and Disposal

- Check with manufacturer

## Electrical

Capacity (typical)	14Ah @ 3A & RT
Energy (typical)	200Wh
Max. voltage	16.8V
Nom. voltage	14.4V
Min. voltage	10V
Max. Dis. Current (cont.)	10A
Communication	One-wire/SMBus; LED SOCi
Life Cycle	300 cycles to 80% of initial capacity @ 100% DOD

## Mechanical

Dimensions	(L,W,H; mm) 197 X 152 X 24
Weight	1000 gr
Energy Density	200Wh/kg;
Battery Housing	Semi-Flexible elastomer
Color	Grey / Customized

## Environmental

Charge	0°C to 45°C
Discharge	-34°C to 60°C
Storage	-20°C to 50°C
Humidity	0 to 90%
Transportation	Class 9

