



DATA SHEET



NAME	BATTERY CAPACITOR
ITEM	2.7V 9000F(Ø35 × L82) Part No. CB2R7908W35082SNBHE
APPLICATION	-
REMARK	-
COMPANY	SAMWHA CAPACITOR
TEL	82 31 330 5929
ADDRESS	227, Gyeonggidong-ro, Namsa-myeon, Cheoin-gu, Youngin-si, Gyeonggi-do, Korea





CB2R7588W35082SNBHP


Item	Unit	Specification
Capacitance (25℃, 2.7~1.6V)	F	9000
Capacity(25℃, 2.7~1.6V)	Ah	3.7
Usable Energy Density(25℃, 2.7~1.6V)	Wh	8.3
Rated Voltage, V_R	V	2.7
Max. Continuous Current	A	12
Max. Peak Current	A	25
ESR (DC / AC,1kHz)	mΩ	<7.5/ <5
Usable Specific Power(P_d)	W/kg	480
Dimensions	mm	35Φ x 82mm
Weight	kg	0.144
Operating Temperature Range	℃	-20 ~ +50
Capacitance Change	%	Within ±40% of initial value
Internal Resistance Change	%	Within ±200% of initial value
Max. Leakage Current, L_C (after 72h)	mA	<15
Cycle Life(25℃)	cycle	15,000

1. Electrical Performance

No	Item	Unit	Specification	Test Conditions and Methods
1	Capacitance at 20°C	F	9000	 <p>[Samwha Standard]</p> $C = \frac{I \times (T_2 - T_1)}{V_R - V_L} \quad (F)$ <ol style="list-style-type: none"> 1) Charging is performed by constant current of 1mA/F. 2) Charging is performed for duration of 30 minutes a rated voltage. 3) Discharge use a constant current load device and measure the time for the terminal voltage from V_R to V_L at the current density of 1mA/F.
2	Capacitance Tolerance at 20°C	%	-0 / +20	-
3	Rated voltage	V	2.7	-
4	Leakage current after 72 hour	mA	<15	 <p>[Samwha Standard]</p> <p>The battery capacitor is charged with the rated voltage for 72hrs. Then, leakage current is measured by current measurement equipment.</p>

No	Item		Unit	Specification	Test Conditions and Methods
5	Internal resistance (ESR)	DC	mΩ	<7.5	<p>[Samwha Standard]</p>  $R_D = \frac{\Delta U_3}{I}$
		AC 1kHz	mΩ	<5	<p>[IEC 62391-1]</p>  $R_A = \frac{\Delta U}{I}$ <ol style="list-style-type: none"> 1) The internal resistance R_A of a capacitor shall be calculated by the above formula. 2) The frequency of the measuring voltage shall be 1kHz. 3) The AC current shall be from 1mA to 10mA.
6	Operating temperature		°C	-20 ~ +50	Operating temperature range shall be -20 ~ +50°C.
7	Energy density	Gravimetric	Wh/kg	58	2.7~1.6V
8	Power density	Gravimetric	W/kg	820	-

2. Reliability

No	Item		Unit	Specification	Test Conditions and Methods										
1	Temperature Characteristic	Capacitance change	%	Within $\pm 40\%$ of initial specified value at $+20^\circ\text{C}$	<p>[Samwha Standard]</p> <table border="1"> <thead> <tr> <th>Temperature($^\circ\text{C}$)</th> <th>Keep Time</th> </tr> </thead> <tbody> <tr> <td>$+ 20 \pm 2$</td> <td>-</td> </tr> <tr> <td>$- 20 \pm 2$</td> <td>2 hr</td> </tr> <tr> <td>$+ 20 \pm 2$</td> <td>15 min</td> </tr> <tr> <td>$+ 50 \pm 2$</td> <td>2 hr</td> </tr> </tbody> </table> <p>Measure electrical characteristics after exposing capacitor to each temperature atmosphere for 2 hours or 15min.</p>	Temperature($^\circ\text{C}$)	Keep Time	$+ 20 \pm 2$	-	$- 20 \pm 2$	2 hr	$+ 20 \pm 2$	15 min	$+ 50 \pm 2$	2 hr
		Temperature($^\circ\text{C}$)	Keep Time												
$+ 20 \pm 2$	-														
$- 20 \pm 2$	2 hr														
$+ 20 \pm 2$	15 min														
$+ 50 \pm 2$	2 hr														
		Internal resistance change	%	Within $\pm 200\%$ of initial specified value at $+20^\circ\text{C}$											
2	Shelf life after 1000 hours no load test same as endurance		%	Same as endurance	<p>[Samwha Standard]</p> <p>Temperature : $50 \pm 2^\circ\text{C}$ Duration : $1000 +72/-0$ hour</p>										
3	Cycle life (at 25°C)	Cycle	Cycle	15,000	<p>[Samwha Standard]</p>  <p>where U_R is the rated voltage of 2.7V U_L is the low voltage of 1.6V</p> <p>Condition the capacitor at $25 \pm 3^\circ\text{C}$ until thermal equilibrium is reached. Initialize the voltage on the capacitor at U_L(1.6V). Then charge the capacitor at a current 8A to U_R. Maintain voltage U_R on the capacitor for 10 ± 0.50 s. Then discharge the capacitor to U_L at current 8A. Hold at U_L for 10 ± 0.50 s. This defines a cycle(see Figure). Repeat this cycle throughout the testing.</p>										
		Capacitance change	%	Within $\pm 40\%$ of initial specified value											
		Internal resistance change	%	Within $\pm 200\%$ of initial specified value											

No	Item	Unit	Specification	Test Conditions and Methods	
4	Damp heat	Capacitance change	%	Within ± 30 % of initial specified value	[Samwha Standard] Temperature : $50 \pm 2^\circ\text{C}$ Relative humidity : 90%~95% Duration : 240 ± 8 hours
		Internal resistance change	%	Within ± 200 % of initial specified value	
5	Resistance to soldering heat	Capacitance change	%	Within ± 10 % of initial specified value	[Samwha Standard] Solder : HSE-02 SR-34 Flux : 25% by weight of rosin in methanol Solder temperature : $260 \pm 5^\circ\text{C}$ Immersion depth : 2.0 mm Immersion time : 10 ± 1 sec. Immersion speed : 25 ± 2.5 mm/sec.
		Internal resistance change	%	Within ± 200 % of initial specified value	

3. Dimensions

Part number	Capacitance (F)	Dimension(mm)			
		D (Φ) ± 1	L (mm) ± 2	g (mm) ± 0.2	t (mm) ± 0.1
CB2R7908W35082SNBHE	9000F	35	82	10	0.8

